



**ZBSMP-PW**  
PowerPad Deactivator

## PowerPad Deactivator

The Sensormatic PowerPad Deactivator offers superior deactivation reliability at impressive throughput speeds. The PowerPad deactivates active AM EAS labels up to 17.5cm (7in) above its surface at a throughput speed of up to 200cm/sec (80in/sec) — allowing deactivation of both source-tagged and retailer-tagged merchandise.

Designed to accommodate various checkstand configurations, the PowerPad can be installed on or below the counter, or at the counter's edge with brackets. The optional Remote Alarm Module can be mounted almost anywhere on the checkstand. The alarm module provides audible and visual confirmations when active labels are detected and deactivated. The locking key feature within the alarm module, prevents unauthorized use of the PowerPad when point-of-sale is unattended.

When connected to a compatible EAS data management device, real-time deactivation counts can be generated into user-friendly customizable reports to provide business-critical data.

### Retailer Values

- // Flexible installation options accommodate a variety of checkstand configurations
- // Fast deactivation accelerates check-out and alleviates unnecessary shopper delays
- // EAS connectivity option allows generation of operational information to help quickly identify and correct performance issues
- // Built-in audible and visual indicators provide immediate feedback when active labels are detected and deactivated, enhancing front end productivity

### Product Codes

**ZBSMP-PW**  
PowerPad Deactivator, AMB9010-IPS Controller, Remote Alarm Module, Power Cord

**ZBAMB9010-IPS**  
Controller with Cord

**ZBSMPPP**  
PowerPad Deactivator Only

**ZBSTP-PP-B1**  
Flush Mount Tray

**ZBSTP-PP-B2**  
Under-the-Counter Bracket

**ZBSTP-PP-B3**  
Cantilever Mounting Bracket

### ZBSTP-PP-B4

Flip Mount Bracket

### Product Compatibility

All Sensormatic AM EAS Labels  
Local Device Manager II (LDM II)  
Remote Alarm Module

### Specifications

**Length**..... 39.3cm (15.5in)  
**Width** ..... 17cm (6.7in)  
**Height** ..... 5.7cm (2.2in)  
**Weight** ..... 9.6kg (21lbs)  
**Pad Cable Length**.....3m (10ft)

### Electrical

Requires Universal Controller (ZBAMB9010-IPS)

### Environmental Constraints

**Operating Frequency**  
58 kHz

**Operating Temperature**  
0°C to 40°C (32°F to 104°F)

**CE** This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.