



## Ultra•Strip III Microwavable Roll Label

The Ultra•Strip III Microwavable Label provides premier protection for meat products. This label is designed to be source tagged in meat soaker pads for inconspicuous protection.

### Retailer Values

- // Designed for meat products that will be microwaved
- // Utilizes proven Sensormatic AM technology and manufacturing process to provide the highest in detection performance
- // Works well on liquids, foils and in metal shopping carts
- // Robust construction provides optimal merchandise protection

### Product Codes

ZLDRM7K3

### Technology

AM

### Environmental Constraints

#### Temperature

Maximum storage temperature not to exceed 50°C (122°F) for 96 hours at 80% RH.

#### Humidity

Unaffected by 80% humidity at 50°C (122°F), up to 96 hours.

#### Shelf Life

One year from date of manufacture when labels are stored between 15°C-32°C (60°F-90°F), 30-80% RH.

### Product Compatibility

Sensormatic AM detection and deactivation devices.

### Mode of Application

Automatic

### Materials of Construction

#### Plastic Substrate

Polystyrene 0.3mm (0.012in) 178.2010 and 178.3860

#### Magnetic Acoustic Resonator

Resonant magnetic material. Amorphous alloy based on iron, containing nickel, cobalt, boron and silicon

### Laminate

Low Density Polyethylene/Polyester  
0.119mm (0.0047in)

### Bias

Proprietary semi-hard magnetic material containing iron, nickel and chromium

### Adhesive

Double-coated, rubber-based adhesive:

- // 2.4 mil thick per side
- // Minimum peel strength of 2.27kg/5lbs

### Aluminum

99.45% pure aluminum 0.038mm (0.0015in thick), 12.7mm (0.5in wide)

### Release Liner

Double-sided, silicon-coated liner:  
2 mil polyester

### Dimensions

**Color** ..... White

**Length**.....44.60mm ± 0.15mm  
(1.76in ± 0.006in)

**Width** ..... 10.16mm ± 0.15mm  
(0.400in ± 0.006in)

**Label Thickness**  
(excluding liner)..... Maximum  
1.83mm (0.072in)

**Liner Width** ..... Maximum  
4mm (0.157in)

**Label Repeat** ..... Maximum  
4mm (0.157in)

### Label to Liner

**Spacing** .....2.02mm ± 0.762mm  
(0.08in ± 0.03in)

**Note:** Warranty terms and conditions are as specified in the applicable Sales Agreement.

**CE** The acousto-magnetic (AM) label is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.

See [Sensormatic.com](http://Sensormatic.com) for Usage Instructions

**Additional Consideration:**  
The label must be applied to packaging containing meat weighing at least 227 grams (0.5lbs) or greater to be microwavable

### ROLL SPECIFICATIONS

	Roll		Roll
PRODUCT CODE	ZLDRM7K3	PRODUCT CODE	ZLDRM7K3
Diameter Of Core	152.4mm (6in)*	External Carton Dimensions	51.8 x 51.8 x 25.4cm (20.38 x 20.38 x 10in)
Max Roll Diameter	7000 unit roll	External Cubic Ft. Per Case	2.4
Number Splices	6 splices, 1 leader splice	Rolls Per Case	4
Roll Weight	4.09kg (9.02lbs)	Cases Per Pallet	16
Case Weight	17.77kg (39.18lbs)	Order Multiple	7,000-unit roll

\*Including 3in core adapter