



Ultra•Strip III Non-Reactivatable Sheet Label

The Ultra•Strip III Non-Reactivatable Sheet Label provides premier performance and merchandise protection. Applied at the point of manufacturing, this label remains with the product after purchase. The non-reactivatable design prevents inadvertent reactivation after customer purchase.

Retailer Values

- // Utilizes proven Sensormatic AM technology and manufacturing process to provide the highest detection performance
- // Non-reactivatable format helps prevent inadvertent reactivation, reducing nuisance EAS alarms at the store entrance
- // Merchandise arrives sales-floor ready, enabling immediate product availability

Solution Application

Footwear

Product Codes

ZLAML-DRDBS6

Technology

AM

Environmental Constraints

Temperature

Maximum storage temperature not to exceed 50°C (122°F) for 96 hours at 80% RH

Humidity

Unaffected by 80% humidity at 50°C (122°F), up to 96 hours.

Shelf Life

Two years from date of manufacture when labels are stored between 15°C-32°C (60°F-90°F), 30-80% RH.

Product Compatibility

Sensormatic AM detection and deactivation devices

Mode of Application

Hand

Materials of Construction

Plastic Substrate

Polystyrene/Polyethylene 0.3mm (0.012in) thick

Magnetic Acoustic Resonator

Proprietary resonant magnetic material. Amorphous alloy based on iron, containing nickel, cobalt, boron and silicon

Laminate

Low Density Polyethylene/Polyester 0.101mm (0.004in)

Bias

Proprietary semi-hard magnetic material containing iron, nickel and chromium

Adhesive

- Double-coated, rubber-based adhesive:
- // 2.4 mil thick per side
- // Minimum peel strength of 80oz/in

Release Liner

Double-sided, silicon-coated 80lb bleached kraft liner 0.114mm (0.0045in) thick

Dimensions

Color	White
Length	45.21mm + 0.5mm (1.78 + 0.020in)
Width	10.67mm + 0.5mm (0.420in + 0.020in)
Label Thickness (excluding liner)	Maximum 1.89mm (0.074in)
(including liner)	Maximum 2.00mm (0.079in)
Labels Per Sheet	108

Note: Warranty terms and conditions are as specified in the applicable Sales Agreement.

CE The acousto-magnetic (AM) label is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.

See Sensormatic.com for Usage Instructions

SHEET SPECS	
	Sheet
PRODUCT CODE	ZLAML-DRDBS6
Case Weight	3.69kg (8.12lbs)
External Carton Dimensions	27.9 x 20 x 11cm (11 x 8 x 4.5in)
External Cubic Ft. Per Case	0.23
Labels per sheet	108
Order Multiple	5,000-unit case